

INSTALLATION INSTRUCTIONS & CODE CHANGE INSTRUCTIONS



Digital Lock




SPECIAL NOTES

You are advised to familiarise yourself with the instructions before starting work.


- The 'hold-open' model is equipped with a snib on the backplate. This enables the latchbolt to be held open when required.
- Before commencing installation check that all parts are working correctly. Press the code according to the code card and ensure the knob turns and returns easily under spring pressure. If you have a key override lock, try the keys to ensure that they turn in the knob handle.
- If you intend to change the code, it should be done before installing the lock. See the code change instructions on the other side of this leaflet.
- Make sure that the lever handle of the backplate moves freely. If your lock is a 'hold-open' model then check that the snib will engage and hold the handle in the 'latch-open' position.
- Check that the latch bolt moves freely by pressing at the end and also by turning the flat spindle in the latch cam.

1. CHECK THE HAND OF YOUR DOOR



Viewed from outside, a door is right handed if the hinges are on the right, and left handed if the hinges are on the left.

2. APPLY THE TEMPLATE




- Crease the template along the line marked 'Fold along the edge of the door', and tape it to the door.
- Mark the 13mm hole and the 3 x 8mm holes. Mark the centre line of latch in the middle of the door edge. Now apply the template to the other side of the door, aligning it with your first mark in the middle of the door edge. Mark the 4 holes again.
- Keeping the drill level and square to the door, drill holes from both sides to avoid splintering out of the door face.

Positioning and fixing the latch

- Mark a central point on the 'centre line of latch' on the door edge.
- Mark the depth of 85mm on the drill bit with tape to act as a visible depth limit. Drill a 25mm hole, 85mm deep, keeping the drill level and square to the door.
- Insert the latch into the hole, and with the edges parallel to the door, draw around the face plate.
- Remove the latch. Score the pencil line with a Stanley Knife to avoid splitting prior to chiselling. Chisel a 3mm rebate to fit the latch face flush to the door edge.
- Fix the latch with the wood screws, with the bevel towards the door frame.

3. LATCH SUPPORT POST




- Fit the Latch Support Post in the back of the lockcase, using Hole A for a Right Hand door or Hole B for a Left Hand door.

4. HOLD-OPEN BACKPLATE


- The backplate of a hold-open lock is fitted with a blue screw to stop the handle moving in the wrong direction. This should be in the Left Hand hole for a Right Hand door, or the Right Hand hole for a Left Hand door.

5. POSITIONING THE SPINDLE




- The spring-loaded spindle will fit doors between 35mm and 65mm thick. For doors less than 50mm thick break off the 15mm section at the end of the spindle. For doors more than 65mm thick, contact your local stockist for advice. The spring keeps the spindle firmly engaged in the outside handle when the lock is assembled on the door.
- Insert the spindle (with the spring on the code side) through the 13mm hole in the door and make sure that it engages the latch correctly for the hand of the door (see FIG. 1).

6. FIXING THE LOCK




- Cut the fixing bolts to suit the door thickness, allowing at least one threaded section to screw into the lockcase.
- Hold the lock case and the backplate (including the seals) onto the door with the spindle in position.
- Use the fixing bolts to screw everything together through the top and bottom holes of the backplate. Before tightening make sure that the lock is vertical and test the mechanism to ensure that it is all moving easily. **DO NOT CLOSE THE DOOR UNTIL YOU ARE SURE THAT THE CODE WORKS.** **DO NOT** over-tighten the fixing bolts as this may cause distortion and lead to poor operation.

7. FITTING THE STRIKE PLATE



NB The plunger beside the latchbolt deadlocks the latchbolt and protects it against manipulation. **IT MUST NOT** enter the strike plate aperture when the door is closed.




- Ensure there are no obstructions to prevent the door closing properly into its frame such as litter trapped in the hinge side.
- Position the strike plate on the door frame so that it lines up with the flat of the latchbolt, **NOT THE PLUNGER**.
- Draw around the aperture of the strike plate. Chisel out the aperture 15mm deep to receive the latchbolt. Fix the strike plate to the surface of the frame with one screw only. Close the door and ensure that the latch bolt enters the aperture easily, and is held without too much 'play'. When satisfied, draw around the final position of the strike plate, remove it and cut a 1mm rebate to enable it to fit flush. Re-fix the strike plate with both screws.


CODE CHANGE INSTRUCTIONS

1. Take your AS2000 or AS2100 lock off the door by unscrewing the 2 screws in the backplate.
2. Press the C button to reset the chamber and place the lock case on a flat surface with the buttons down.
3. Remove the 2 red screws and carefully lift off the code chamber plate. Check that all 14 springs are held in place on the plate.
4. Note that the red tipped code tumblers correspond in position to the existing code. The blue tipped non-code tumblers fill the other positions. The C tumbler is not coloured.
5. Hold the lock in your hand and depress the C button. Keeping the C button depressed use tweezers to re-position the tumblers to correspond with your new code. The square notches of ALL tumblers **MUST** face outwards, with the coloured tips **ON TOP**: See diagram below. **DO NOT** force the tumblers in.

NB: Holding the C button depressed whilst re-positioning the tumblers is **ESSENTIAL** to avoid damaging the internal mechanism. **DO NOT** attempt to reposition the C tumbler.



6. Replace the code chamber plate carefully with the 2 red screws.
7. Check the operation of the new code, and make a written note of it before re-installing the lock.
8. Insert the spindle with the spring on the code side. On latchbolt locks the spindle must engage the latch as follows:



MAINTENANCE

No maintenance of the working parts is necessary. **DO NOT OIL.** To maintain the finish the lock should be cleaned regularly with a soft cloth. A silicone spray or similar should be used to provide a protective film against grit and grime.

5-Year Mechanical Warranty

We will repair and return your Asec digital lock up to 5 years after purchase. If the unit is beyond economical repair then a replacement unit / refund will be issued at the suppliers discretion.

- I) The unit must be installed in a correct application, e.g. not excessive daily usage.
- II) Any faults caused through malicious damage, incorrect code change or re-assembly shall invalidate the warranty.

Should you wish to return a unit under warranty please return it to the point of purchase along with proof of purchase.