

Autolok[®]

Fitting Instructions for the Autolok Telescopic Security Post


Part Number KTARP

Thank you for choosing the Autolok telescopic security post. Please ensure you read these instructions carefully before installing the product.

INSTALLATION

1. Please read **"Important Notes"** below
2. Choose a location for the post ensuring that the post will be free from obstructions in both the raised and lowered positions.
3. Dig the hole 5" (127mm) deeper than the length of the ground socket.
4. The width of the hole should be at least 12" square.
5. For water drainage line the bottom of the hole with either gravel or rubble
6. Position the steel stabilising rod into the holes at the bottom of the post. Place the ground socket into the hole so that the top of the post is at ground level.
7. Wedge the post in position and check that it is vertical, it may help to extend the post to check with a spirit level that the post is vertical. Now retract the post and fill 50% of the hole with hardcore and compact. Check that the post is still vertical and fill the hole with concrete to the surface level.
8. Check that the post is still vertical by extending the post, then retract and leave in the down position for at least 48 hours or until the concrete is fully set.

The Concrete Mix should be a strong mix (i.e. not too wet) we recommend a mix of 1 part concrete to 3 parts aggregate.



"Important Notes" Please read carefully

When deciding the location of the post, look for drainage covers etc and avoid installation between these points to try to prevent uncovering pipes etc. Dig slowly using hand tools so that if you do encounter a pipe or cable you do not damage them. If you do encounter a pipe or cable re-fill and select a new location. If in doubt consult a qualified builder for installation of this product.

Warning: The Autolok Security Post is made of heavy weight steel, to prevent injury to your fingers or hand, please hold the handle at the top of the post when removing the padlock and ensure that the post is lowered slowly into the ground.

The manufacturer reserves the right to amend the product specification at any time. This product carries a 12 month guarantee against manufacturing defects, in the unlikely event that a fault should occur, please contact our Customer Service on 0161 624 8171

The Autolok security post has been designed to act as a deterrent against theft, however theft can occur even though various security devices are fitted.

This does not effect your statutory rights

Autolok Security Products Limited, Park Lane, Royton, Oldham, OL2 6PU, UK